



# port-a-cool®

portable evaporative cooling units

**WAREHOUSES • INDUSTRIAL • AUTO SHOPS • ANYWHERE IT'S HOT!**

PORT-A-COOL® portable evaporative cooling units are completely self-contained, offering many versatile options for effective cooling when standard air conditioning may be unavailable, impractical or cost-prohibitive.

Requires only tap water and 110 volts to deliver cool air an average of 20° lower than surrounding air.

• *Environmentally Friendly* • *Energy Efficient*

• *No Mist! Just Cool Air* • *Safe for Equipment* • *Available in Four Sizes*

## Port-A-Cool® Unit Replacement Pads

Pads are produced using Thru-Cure™, a unique, patent pending process developed by the manufacturer. Thru-Cure™ ensures the complete resin cure in each sheet of virgin kraft paper.



PAC2K363S



PAC2K482S



PAC2K163SFC



PAC2K163SHD



PAC-ACC-01

50-gal. water tank with dust cover for use with Port-A-Cool® units.


## EVAPORATIVE COOLING FAN ORDERING DATA

MODEL	BLADE SIZE	SPEED	CFM	FAN MOTOR	PUMP	WATER RESERVOIR	EVAPORATION MEDIA	DIM.	UNIT WT.	SHIP. WT.
PAC2K361S	36"	1-SPD	9600	1/2 HP 115V 7.4AMP	1/6HP 115V 5 AMP	20 GAL.	48"H X 60"W X 6"D	67"H X 62"W X 32"D	195 LB.	235 LB.
PAC2K363S	36"	3-SPD	4800/6600/9600	1/2 HP 115V 6.5AMP	1/6HP 115V 5 AMP	20 GAL.	48"H X 60"W X 6"D	67"H X 62"W X 32"D	205 LB.	245 LB.
PAC2K36HPVS	36"	Variable-SPD	10,100	1/2 HP 115V 6.3 AMP	1/6 HP 115V 5 AMP	20 GAL.	48"H X 60"W X 6"D	67"H X 62"W X 32"D	205 LB.	245 LB.
PAC2K24HPVS	24"	Variable-SPD	6700	1/3 HP 115V 4.5 AMP	1/6HP 115V 5 AMP	14 GAL.	36"H X 48"W X 6"D	53"H X 50"W X 25"D	155 LB.	180 LB.
PAC2K163SHD	16"	3-SPDHD	2500/3280/3900	1/2 HP 110V 3.4 AMP	1/70 HP 115 VAC 0.92 AMP	3 GAL.	36"H X 36"W X 6"D	30"H X 37"W X 22"D	70 LB.	80 LB.
PAC2K163SFC	16"	3-SPDHD	2500/3280/3900	1/2 HP 110V 3.4 AMP	110V/60HZ/1.7AMP SUB.	22 GAL.	24"HX12"WX6"D	60"HX39"WX24"D	115 LB.	145 LB.
PAC2K482S	48"	2-SPD	11000/17000	1 HP 115/230 V 8.7 AMP	1/6 HP 115V 5AMP	25 GAL.	60"H X 72"W X 6"D	86"H X 74"W X 36"D	345 LB.	415 LB.
PAC-ACC-01	-	-	-	-	-	50 GAL.	-	41"H X 20"W X 36"D	-	72 LB.

## Port-A-Cool® Unit Replacement Pads

Pads are produced using Thru-Cure™, a unique, patent pending process developed by the manufacturer. Thru-Cure™ ensures the complete resin cure in each sheet of virgin kraft paper.

Description	Dimensions (In.)			Pads per Unit	Stock #
	H	W	D		
48" Port-A-Cool® unit	60	12	6	6	PAD6060
36" Port-A-Cool® unit	48	12	6	5	PAD6048
24" Port-A-Cool® unit	36	12	6	4	PAD6036
16" Port-A-Cool® unit	24	12	6	3	PAD6024




**Dallas**  
**PORT-A-COOL**  
*Evaporative Cooling -  
Anywhere It's Hot!*

**1045 S. Jupiter • Garland, Texas 75042**  
**972-276-6628 • fax 972-272-9938**  
**Toll-Free 1-877-BIG-OFAN (1-877-244-6326)**  
**www.bigofan.com • sales@bigofan.com**